

Gas detectors

EX 2000/EX 2000 C/ GD 2000/GDP 2000

**Explosimeters/
Catharometers**

■ ■ ■ *Gas Discrimination
(GD 2000 / GDP 2000)*

■ ■ ■ *Pocket size*

■ ■ ■ *Long battery life*

■ ■ ■ *High reliability*

■ ■ ■ *New design for Enhanced
performance*



Let's protect your personnel together



Going down a confined space

You work in industrial hazardous areas likely to contain explosive gases and vapors. Oldham have designed a new explosimeter range to suit your requirements. We are aware of the potential risks that you face and identify the type of gas to ensure a total safety package.

One of the smallest explosimeters on the market, with the best performance, the EX 2000, EX 2000 C, the GD 2000 and GDP 2000 identify the detected gas and the GDP 2000 displays its concentration level. Even more, they can discriminate between natural gas and other explosive gases. Light, practical and high-performance, the 2000 range of explosimeters are the ideal, compact gas detectors for industry.

A tremendous efficiency

Smart sensor



Scale 1:1

Practical and modern design

The 2000 Range of explosimeters are designed to ensure a total freedom in your personal activity :

- ergonomic keyboard : 3 tactile buttons
- high Visible alarm
- light weight

High reliability

The high quality detection sensor ensures measurement accuracy.

The technique offers several advantages :

- exceptional response time
- 30 battery life hours
- poison resistance

Standards

Our explosimeters are in accordance :

- with the European certification :
 - surface : EEx iad IIC T4
 - mine : EEx iad I
- with the North American certification :
 - class I groups A, B, C, and D



Toxic products storage room

The 2000 Range of explosimeters are designed to minimize problems.

Long battery life

- 12 hours with rechargeable batteries (Ni-Cd or Ni-mH)
- 30 hours with dry cell batteries
- Simple charger
- “Intelligent” two position charger
- 12 VDC charger

Pocket size

Maintenance and calibration very easy, simple and safe

Friendly display panel



2 position charger CR2002

Visual and audio alarms

- Red light flashing
- Pulsed alarm : 1 beep every 2 seconds for the first alarm threshold
- Pulsed alarm : 1 beep every 1 second for the second alarm threshold
- Adjustable alarm thresholds

Auto operation status

- Auto test when switching on
- Auto diagnosis
- Confidence beep
- Battery and sensor faults
(audio and visual alarm, continuous + pictograms displayed)



Main characteristics

EX 2000

To measure the explosive gas concentration

- Detects all types of explosive gases
- Displays 0-100% LEL
- Can be programmed for a selected gas



EX 2000 C

To measure the concentration of explosive gases

- Only one detection sensor
- Detects and displays low concentration (0-100 LEL) and high concentration (0-100 %vol)
- Automatic switch over of range (catalytic or catharometric)



GD 2000

To discriminate between natural gas and other explosive gases

- Detects all types of explosive gases with discrimination
- Displays simple messages for the user ie :
 - "OK" for "no gas detected"
 - "NATURAL GAS" or "FLAMMABLE GAS"



GDP 2000

To discriminate between natural gas and other explosive gases, and to display the gas concentration

- Detects all types of explosive gas with discrimination
- Displays simple messages for the user ie :
 - "OK" for "no gas detected"
 - "Nat G" for « NATURAL GAS » or "FLM G" for « FLAMMABLE GAS » with the gas concentration detected in % LEL



Options available

- 1 Protective leather case
- 2 Remote sampling kit
- 3 Calibration kit
- 4 ATEX electric pump
- 5 Chargers



Portable gas detectors

Technical characteristics

Type	EX 2000	EX 2000 C
Manufacturer	• OLDHAM SA	
Function	• Explosimeter	• Explosimeter and catharometer
Detected gases	• Explosive gas (%LEL)	• Explosive gas 0-100% LEL and 0-100% v/v gas
Mode	• Continuous	
Display	• Gas detected value displayed	• Gas detected, value displayed • Automatic switch from the catalytic range to the catharometric range
Display panel	• Lighting up of LCD panel on request	
Message displayed	• The gas detected value	• The gas detected value
Out of order		
Sensor fault	• Both visual and audible continuous alarms + pictograms	
Battery fault	• Both visual and audible continuous alarms + pictograms	
Operating check	• Correct operation "beep" signal that the manufactory can adjust or cancell on request	
Alarms		
Gas alarm	• Instantaneous and adjustable threshold • A pre-programmed instantaneous alarm threshold • Over scale alarm	
Visual alarm	• A red flash alarm • Pictograms for each alarm type	
Audio alarm	• Buzzer 85 db at 30 cm	
Power supply	• 3 batteries R6 1,5 V • 3 accus Ni-mH	• 3 batteries R6 1,5 V • Ni-Cd or Ni-mH
Battery lifetime	• 22 h with accus Ni-mH • 30 h with batteries	• 22 h with Ni-mH • 30 h with dry cell batteries
Recharging time	• 4 h (auto adjusted charger) • 16 h (simple charger)	• 4 h (auto regulated charger) • 16 h (simple charger)
Protection rating	• IP 66	
Housing	• Antistatic polycarbonate	
Weight	• 230 g	
Type of clips	• Anti-sliping metallic clip	
Working temperature	• -25°C to +55°C	• -15°C to +45°C
Dimensions	• 144 x 55 x 30 mm	
Approval	• EEx iad IIC T4 INERIS 98 D 5022 X Surface • EEx iad I INERIS 98 Y 3001 X Mine • INERIS 02ATEX0060 • CSA class I groups A, B, C, D	
Sensor characteristics		
Type	• Plug-in catalytic	• Plug-in catalytic-catharometric
Standard range	• 0-100 % LEL • 0-5 % CH4	• 0-100% LEL or 0-5% CH4, 0-100% v/v
Accuracy	• +/-1 % LEL or +/- 3 %	• +/-1% LEL or +/-3%
Minimum detected	• 1 % LEL	• 1 % LEL
Zero drift	• < 1 % of full scale per month	• 0,5% LEL methane per month
Response time	• < 20 seconds at T90	
Average lifetime	• 4 years (for normal operation)	

OLDHAM
Belgium

☎ (33) 03 21 60 81 20
☎ (33) 03 21 60 81 02
oldham.belgium@oldham.fr

OLDHAM
Italia

☎ 011-3801371
☎ 011-3806613
info@oldham.it

OLDHAM
Česká Republika

☎ 420 234 622 222/3
☎ 420 234 622 220
oldham@oldham.cz

OLDHAM
Romania

☎ (40) 21 222 4846
☎ (40) 21 222 5037
oldham@fx.ro

OLDHAM
Switzerland

☎ (41) 26 652 51 18
☎ (41) 26 652 51 19
info@oldham.ch


OLDHAM
United Kingdom

☎ (44) 0 1782 562002
☎ (44) 0 1782 564414
sales@oldham.biz

OLDHAM
Deutschland
WINTER

☎ (49) 231 924 10
☎ (49) 231 924 125
info@winter-gmbh.com

GD 2000	GDP 2000
• OLDHAM SA	
• Explosimeter	• Explosimeter
• Natural gas, explosive gas	• Natural gas, explosive gas : 0-100% LEL
• Continuous	
• Type of gas detected	• Gas type detected and value displayed
• Lighting up of LCD panel on request	
• "OK", "gas NATURAL", "gas EXPLOSIVE"	• "gas NATURAL", "gas EXPLOSIVE" • Gas detected value
• Both visual and audible continuous alarms + pictograms	
• Both visual and audible continuous alarms + pictograms	
• Correct operation "beep" signal that the manufactory can adjust or cancell on request	
• A 5 % LEL gas naturel threshold • A 20%LEL natural gas threshold • A 20% LEL threshold, butane equivalent	• An early-warning alarm for natural gas • A "NATURAL gas" alarm threshold • Over scale alarm • Over scale alarm
• A red flash alarm • Pictograms for each alarm type • Buzzer 85 db at 30 cm • 3 batteries R6 1,5 V • Ni-mH • 22 h with Ni-mH • 30 h with dry cell batteries • 4 h (auto regulated charger) • 16 h (simple charger)	
• IP 66	
• Antistatic polycarbonate	
• 230 g	
• Anti-slipping metallic clip	
• -25°C to +55°C	• -25°C to +55°C
• 144 x 55 x 30 mm	
• EEx iad IIC T 4 INERIS 98 D 5022 X Surface • EEx iad I INERIS 98 Y 3001 X Mine • INERIS 02ATEX0060 • CSA class I groups A, B, C, D	
• Precalibrated plug-in catalytic	
• 0-100% LEL natural gas • 0-100% LEL butane (standard)	• 0-100 % LEL • 0-100% LEL other gases
• +/-1% LEL or +/- 3%	• +/-1% LEL or +/- 3%
• 1 % LEL	• 1 % LEL
• 0,5% LEL methane per month	• < 1 % of full scale per month
• < 20 seconds at T90	
• 4 years (for normal operation)	



**Explosimeters/
Catharometers**



Your agent or retailer



Plant and head office : Z.I. Est - rue Orfila
B.P. 417 - 62 027 ARRAS Cedex FRANCE
Tel. : 33 3 21 60 80 80 Fax : 33 3 21 60 80 00
Web site : <http://www.oldhamgas.com>